



ERGONOMICS

- Control panel located on the applicator arm, easy to adjust
- 4 m hose, articulated arm enabling the operator to cover a wide working area with minimum effort
- Mixing head to ensure the right mix of components and durability



SIMPLICITY

- Easy to fit on a two-axle truck
- Quickly removable to make the truck available for other applications
- Operates independently of the truck with its auxiliary engine



ECONOMY

- Easy heating and temperature maintenance thanks to tank insulation
- Can load up to 1,000L of emulsion and 6m³ of chips to reduce the number and time of refill operations
- Apply just the right quantity with the mixing head, no premix, no wasted materials



RELIABILITY

- Your EASYPATCHER project is developed, designed and produced in our factory in Cossé le Vivien 53 France
- Hotline, in stock spare parts, we remain at your service to ensure the smooth running of your jobsites



COMPACTNESS

- Can be shipped in a container
- One machine for 4 operations
- Application lance can be fully folded into the truck's dimensions
- Mounted on a truck 2 axles or a trailer



EFFICIENCY

- Less than 2 minutes to treat a pothole
- 4 steps for a lasting repair
- Reduced treatment time = more potholes treated per day

- 1) Cleaning the defect by blowing air,
- 2) tack coating the defect « spraying » bitumen emulsion,
- 3) filling the defect with chips having been coated with emulsion,
- 4) finishing the repair with dry chips.









TECHNICAL SPECIFICATIONS



MORE VIDEOS OF OUR PRODUCTS ON OUR YOUTUBE CHANNEL

Assembly

Tank capacity

Tipper capacity

Application arm Auxiliary engine

Auxiliary motor supply

Blower

Compressor

Empty weight

Dimensions

Machine flow

Truck or 2-axle trailer

1,000 L

6m³

Length 4 m - foldable into 3 sections

DEUTZ diesel engine - 32 kW at 2,000 rpm

60 L diesel tank

11 000 L/min @1bar

400 L/min @8bar

2.5 T

Length: 5,893 mm Width: 2,290 mm Height: 2,353 mm

30kg/min

















