

# HANDSEALER

Manual emulsion & chip machine

## SIMPLIFIED JOBSITES: curative maintenance

- ◆ The HANDSEALER is the perfect machine for teams dedicated to road maintenance. Its compactness allows it to access tight work sites and thus allows its operators to efficiently handle localized operations.
- ◆ The HANDSEALER is the perfect partner for any manual repair or surface treatment: potholes, sidewalks or private yards.
- ◆ Like its use, the maintenance of this machine is simplified: quick access, few valves to operate, no mechanical movements.

## BENEFITS:



### COMPACTITY

#### SIMPLIFIED ACCESS TO JOBSITES

- ◆ With its small size, this machine can easily access to tight jobsites
- ◆ 2,500 L tank and 3 m<sup>3</sup> hopper
- ◆ 15 m lance pipe



### EASE OF USE

#### QUICK TO LEARN AND USE

- ◆ Double pick-up bins accessible from the ground
- ◆ Wheelbarrow hatches on both sides of the machine.
- ◆ Ergonomic handlance
- ◆ Easy access to storage box



### VERSATILITY

#### EXTENDED FIELD OF ACTION

- ◆ Possibility of 2 chip size
- ◆ Multi-purpose carrier with TWIST-LOCK or multilift demountable system
- ◆ Variety of application with the 2.5 m spraybar option

## MAIN OPTIONS

**Automatic burner:** A combistat allows the desired binder temperature to be set and the burner to be switched on and off automatically.

This ensures that the binder is always at the desired temperature.

In addition, the electronic ignition of the burner provides safety and convenience.

**Removability :** Thanks to this feature, you can keep your carrier for other uses. Simple and quick, this option will guarantee you more versatility and adaptability in your missions as well as savings linked to the multiple use of the carrier.

**2.50 m spraybar:** With a width of 2.50 m, the spraybar allows you to cover a larger working width than with a handlance. This option brings more safety to your operator who will be operating from the cab and not from the ground.

## TECHNICAL SPECIFICATIONS

Tank capacity	2,500 L
Type of binder	Bitumen emulsion
Type of heating	Manual burner (automatic in option)
Heater	Night heating
Handlance	15 m
Hopper capacity	2 x 1.5 m <sup>3</sup>
Granulometry	Double chip size possible
Hatches	2 chipping bins + 2 wheelbarrow traps
Application	Manual at the back
Removability	Twist-lock or multilift
Drive	Hydraulic pump or diesel engine (6 kW) with electric start

