

GREENSWIFT

SPRAY INJECTION PATCHER FOR CHIPSEALER



ERGONOMICS

- A dedicated GREENSWIFT joystick is positioned on the armrest to complement the SMART CAB joystick.
- Joystick functions: arm control, management of aggregates and emulsion flow rates



SECURITY

- Controlling operations from the cab
- Jobsites in complete safety
- Full folding of the arm behind the truck cab during transfer



ECONOMY

- The functions of a chipsealer combined with a patcher, a single machine, multiple applications
- Only one operator in the cab
- Precise computer-controlled dosages
- Production of the mix according to requirements, no waste of material



RELIABILITY

- Your GREENSWIFT project is developed, designed and produced in our factory in Cossé le Vivien 53 France
- Hotline, in stock spare parts, we remain at your service to ensure the smooth running of your jobsites



VERSATILITY

- Compatible with CHIPSEALER R - A - CT
- Treatment of potholes, craching, peeling, etc.
- 4 functions: air-blowing the area to be treated, spraying bitumen emulsion to waterproof the area, spraying coated aggregates, or only aggregates



EFFICIENCY

- 2 projection speeds: high for better self-compaction & low for better precision
- Possibility to use two sizes of aggregates: adaptation of the constraints of the areas to be treated
- The design of the spray head ensures perfect coating of the aggregates by the emulsion, greater adhesion and a more durable repair

TECHNICAL SPECIFICATIONS

GREENSWIFT is a quality solution for road repairs (potholes, craching, peeling, etc). Indeed, the regulation control of the bitumen emulsion and aggregates mix allows precise dosage guaranteeing works without bleeding. Furthermore, the spraying head's design guarantees that aggregates are perfectly coated avoiding aggregate loss but also offering the most durable repair.

The GREENSWIFT is available in different versions:

- ◆ Basic spray injection patcher
- ◆ Spray injection patcher combined with a simultaneous sprayer-spreader, to allow optimized use of the machine.



MORE VIDEOS OF
OUR PRODUCTS
ON OUR YOUTUBE
CHANNEL

Aggregate type	Single or double grade (from 2 mm to 10 mm)
Binder type	Emulsion only
Operation	100% in cab
Front operation	5 meters
Width operation coverage	7,7 meters
Air Blower	10 m³/min
Aggregate flow rate	De 10 kg/min à 60 kg/min
Aggregate flow rate	100% automatic
Compatible machines	CHIPSEALER R - CHIPSEALER A - CHIPSEALER CT



SECMAIR - Rue Auguste et Louis Lumière - 53230 Cossé-Le-Vivien
Tel. +33 (0)2 43 98 27 76 - Fax +33(0)2 43 98 86 49
info@secmair.fayat.com - secmair.fayat.com

