



EUROSPRAYER

SIMPLICITY

ROBUSTNESS



VERSATILITY

- Spray hot binders (180°C fluxed bitumen, ...) as well as bitumen emulsions (80°C maxi)
- Surface dressing, tack coat and priming
- Spraying with spraybar or hand lance



RELIABILITY

- Your EUROSPRAYER project is developed, designed and produced in our factory in Cossé le Vivien 53 France
- Hotline, in stock spare parts, we remain at your service to ensure the smooth running of your jobsite



ERGONOMICS

- Joystick control: nozzles selection, spraybar position, spraying activation
- Ergonomic screen to access to the different informations: dosing, spraybar width, working speed and jobsite history (distance covered, quantity of emulsion sprayed)



SIMPLICITY

- 3 parts foldable spraybar
- Minimum number of complex components
- Quick access to the different control and component



ECOLOGY

- Tank insulation with rockwool layer with high density: less energy needed to heat and maintain temperature
- Precise dosing and transversal distribution: apply the right quantity
- Binder circuit emptying by sucking and return to the tank, no waste on the ground



CUSTOMISATION

- Truck 2/3/4 axles
- Tank capacity 7,000 à 19,000 L
- Options : automatique burner, telescopic spraybar, water-fuel supply
- Many combinations to suit your needs on your jobsites

MAIN OPTIONS

Automatic burner: A combistat allows the desired binder temperature to be set and the burner to be switched on and off automatically.

This ensures that the binder is always at the desired temperature.

In addition, the electronic ignition of the burner provides safety and comfort of use.

Telescopic spraybar: With a width of 4.80 m, the telescopic spraybar allows to cover a larger working width than with a knee spraybar. It allows to deploy only the necessary width, according to the site constraints, which offers an increased manoeuvrability.

Printer: This function allows you to monitor the jobsite and control the quantities applied with your sprayer.

TECHNICAL SPECIFICATIONS



MORE VIDEOS OF
OUR PRODUCTS
ON OUR YOUTUBE
CHANNEL

Type of binder	All types of bituminous binders
Tank capacity	7,000 L 10,000 L 13,000 L 16,000 L
Isulation	100 mm Duralinox cover
Type of heating	Direct with manual or automatic burner
Dosing range	From 0,1 to 2 kg/m ²
Pump	Immerged pump Max flowrate of 35 m ³ /h driven by a hydraulic motor
Spraybar	4,20 m (foldable) à 4,80 m (telescopic)
Hand lance	5 m
Truck	2/3/4 essieux
Control	In cab Joystick with screen and automatic dosage control

